



Specifications Multipack 4x Ledvance  
LED Downlight Slim Round DN210  
18W 1530lm 120D - 840 Cool White |  
225mm

[View Product](#)

## General Information

|                      |                                                   |
|----------------------|---------------------------------------------------|
| SKU                  | 253048                                            |
| EAN                  | 8719157059442                                     |
| Manufacturer Code    | 8719157059442                                     |
| Brand                | Ledvance                                          |
| Manufacturer Name    | Multipack 4x DL SLIM DN210 18W/4000K WT IP20 LEDV |
| Budgetlight warranty | 3 Years                                           |
| Average Lifetime (h) | 30000                                             |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Emergency Lighting          | No              |
| Tiltable                    | No              |
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x18            |
| Wattage                     | 18W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |

|                       |                                       |
|-----------------------|---------------------------------------|
| Light Colour Options  | Single Color                          |
| Beam Angle (degree)   | 120                                   |
| Luminous Flux (Lumen) | 1530lm                                |
| Lumen per watt        | 85                                    |
| Powerfactor           | >0.50                                 |
| Unified Glare Rating  | < 28 - for hallways and storage rooms |
| Optische Afdekking    | PC (Polycarbonate)                    |
| Type product          | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 210                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Bedrijfstemperatuur    | -20 to +50                    |
| Housing                | PC (Polycarbonate)            |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Product Serie          | DOWNLIGHT SLIM                |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 30  |
| Diameter (mm) | 225 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor

 **Easy** return process

No Sensor



Long-life **LED solutions**